

Spring clips

Now in our program for you – high quality spring clips in different sizes.

The possible applications are extremely diverse: Holding applications for tools of all kinds, component fixtures inside of machines and switchboards, hose routing and safety, as well as effective and inexpensive locking alternatives for doors and valves. If in your workshop or in your product, our spring clips are extremely resilient:


They are made of high quality spring steel and their standard completion is NIROSTA.

Art. no.: GS-291 Spring clip drilled

Material and surface finish:

Raw stainless steel (1.4310)





Article no.			Dimensions in mm										
Series	Execution	Material Stainless steel (Nirosta)	shaft Ø D	D1	D2	Ød	а	b	С	L	S	k	Perforations count
GS-291	-1	-NI	6-8	5,0	8,0	3,1	4,0	13,0	6,0	17,0	0,5	-	1
GS-291	-2	-NI	9-10	6,5	11,0	3,1	5,0	16,0	6,0	21,0	0,5	-	1
GS-291	-3	-NI	11-14	10,0	15,0	3,1	5,0	23,0	8,0	27,0	0,5	I	1
GS-291	-4	-NI	15-18	14,0	19,0	3,1	5,5	26,0	8,0	30,3	0,5	I	1
GS-291	-5	-NI	18-22	15,0	23,0	4,1	6,0	26,5	8,0	39,0	0,5	I	1
GS-291	-6	-NI	23-26	19,0	27,0	4,1	6,5	30,0	8,0	43,0	0,6	I	1
GS-291	-6A	-NI	27-29	21,5	30,0	4,1	8,0	36,5	10,0	51,0	0,7	I	1
GS-291	-7	-NI	30-32	26,0	33,0	5,2	9,0	46,0	13,0	60,0	1,0	-	1
GS-291	-7A	-NI	33-39	30,0	40,0	5,2	10,0	49,5	13,0	64,0	1,0	9	2
GS-291	-8	-NI	39-45	31,0	45,0	5,2	9,0	48	13,0	68,0	1,0	9	2

