

ESN H130/ R60 (verzinkt CrVI-frei passiviert)

Einzelschlitz- auf 2/3 Höhe der Mutter

Gewinde	Artikel Nr.	Abmessungen	
		Höhe	SW
M5	ESNH130M5X80R60Z	6,5	8
M6	ESNH130M6X100R60	7,8	10
M8	ESNH130M8X125R60	10,4	13
M10	ESNH130M10X150R6	13	16
M12	ESNH130M12X175R6	15,6	18
M14	ESNH130M14X200R6	18,2	21
M16	ESNH130M16X200R6	20,8	24
M18	ESNH130M18X250R6	23,4	27
M20	ESNH130M20X250R6	26	30
M22	ESNH130M22X250R6	28,6	34
M24	ESNH130M24X300R6	31,2	36
M27	ESNH130M27X300R6	35,1	41




Sondergrößen (M30-M80) auf Anfrage.

ESN H130/ R80 (verzinkt CrVI-frei passiviert)

Einzelschlitz- auf 2/3 Höhe der Mutter

Gewinde	Artikel Nr.	Abmessungen	
		Höhe	SW
M5	ESNH130M5X80R80Z	6,5	8
M6	ESNH130M6X100R80	7,8	10
M8	ESNH130M8X125R80	10,4	13
M10	ESNH130M10X150R8	13	16
M12	ESNH130M12X175R8	15,6	18
M14	ESNH130M14X200R8	18,2	21
M16	ESNH130M16X200R8	20,8	24
M18	ESNH130M18X250R8	23,4	27
M20	ESNH130M20X250R8	26	30
M22	ESNH130M22X250R8	28,6	34
M24	ESNH130M24X300R8	31,2	36
M27	ESNH130M27X300R8	35,1	41



Sondergrößen (M30-M80) auf Anfrage.